ADELS contact

Screwless Connectors
Block Connectors
930-00/ 7



Terminal Block without Release Keyn, 7 pole, Voltage Rating: 450 V, Current Rating: 24 A, Cross-Section: 2.5 mm²

Order Info

Reference Number (ref. no.)	112007
Applications	Lighting, Electrical Appliances
PU	400
EAN	4028012127368

Type

Type	Terminal Block without Release Keyn
Number of poles	7 pole
Clamping Units per Pole	2
Colour	white
Cross-Section	2.5 mm²
Connection Type	screwless

Technical Data

Voltage Rating	450 V
Current Rating	24 A
Insulating Material	PA 6.6
Contact Material	Brass
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Stripping Length	8.0-9.0 mm
Internal Core Cross-Section max.	2.5 mm²
External Core Cross-Section min.	0.5 mm²
External Core Cross-Section max.	2.5 mm²
Internal Core Cross-Section min.	0.5 mm²
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes
Approbation EN60998	930_935_937_EN60998_20071001_VDE_40022275_web.pdf
Approbation UL	930_935_19880415_19941222_UL_E63492_1-06_Description_web.
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765