
THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.


Rating	**6A 14V DC**
Contact Resistance	**50m ohm max.**
Insulation Resistance	**DC 500V 100M ohm min.**
Dielectric Strength	**AC 1500V 1 minute**
Operating Temperature	**- 0° C ~ 55° C**

Mounting Hole



Cut-Out 0.7 ~ 3.0 mm thk.

Circuit Diagram



SPST (ON) - OFF


(LED)

( )= Momentary

BASE COLOR: Black

BUTTON COLOR: Red, PC Clear

LED: Red



RoHS Compliant

CW INDUSTRIES Southampton, Pa. 18966 Tel 215.355.7080/www.cwind.com	**Date Drawn:** 12/24/09	**Rev.** 0	**Unit:** mm	**Checked By:** G. Guld
	Title: PUSH BUTTON SWITCH		**CW P/N:** GPB554CL05BR	