Product data sheet

Specifications



UPS Communications Cable Smart Signalling 15' / 4.5m

AP9804

Usually in Stock

Overview			
Lead time			

SUB-D 9 male Smart Signaling
15 ft (4.57 m)
_

Connector A SUB-D 9 female Smart Signaling

Mounting Location Front **Product Weight** 0.99 lb(US) (0.45 kg)

Output

Number of port

Environmental

Storage Relative Humidity	095 %	
Storage altitude	050000 ft (0.0015240.00 m)	
Ambient Air Temperature for Operation	32113 °F (045 °C)	
Relative Humidity	095 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	5113 °F (-1545 °C)	

Ordering and shipping details

GTIN	00731304203001
Package weight(Lbs)	0.99 lb(US) (0.45 kg)

Packing Units

Package 1 Height	9.02 in (22.9 cm)
Package 1 width	4.02 in (10.2 cm)
Package 1 Length	2.01 in (5.1 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	2 years repair or replace