


isc Triacs
BTA08-400SW
FEATURES

- With TO-220AB insulated package
- Suitable for general purpose AC switching. Which can be used as an ON/OFF function in applications such as static relays, heating regulation, induction motor starting circuits. Or for phase control operation in light dimmers, motor speed controllers etc.
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

SYMBOL	PARAMETER	MIN	UNIT
V _{DRM}	Repetitive peak off-state voltage	400	V
V _{RRM}	Repetitive peak off-state voltage	400	V
I _{T(RMS)}	RMS on-state current (full sine wave) T _c =75°C	8	A
I _{TSM}	Non-repetitive peak on-state current	80 84	A
		50HZ 60HZ	
T _j	Operating junction temperature	110	°C
T _{stg}	Storage temperature	-40~150	°C
R _{th(j-c)}	Thermal resistance, junction to case	4.4	°C/W
R _{th(j-a)}	Thermal resistance, junction to ambient	60	°C/W

ELECTRICAL CHARACTERISTICS (T_c=25°C unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
I _{RRM}	Repetitive peak reverse current	V _R =V _{RRM} , V _R =V _{RRM} , T _j =110°C	0.01 0.75	mA
I _{DRM}	Repetitive peak off-state current	V _D =V _{DRM} , V _D =V _{DRM} , T _j =110°C	0.01 0.75	mA
I _{GT}	Gate trigger current	I	10	mA
		II	10	
		III	10	
I _H	Holding current	I _{GT} = 0.1A, Gate Open	25	mA
V _{GT}	Gate trigger voltage all quadrant	V _D =12V; R _L = 33 Ω	1.5	V
V _{TM}	On-state voltage	I _T = 11A; t _p = 380 μs	1.75	V