Sparkle Power Inc.
A Leading Power Supply Manufacturer
Web site: www.sparklepower.com

SPI600W7BB

(80PLUS, RoHS Compliant)

600 Watts ATX12V/EPS12V, 2U
Switching Power Supply



Features

- Complied with ATX12V/ EPS12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by : UL/CUL60950-1 2nd TUV EN60950-1 2nd, CB 60950-1 2nd , FCC, EMC

Specification

- **Temperature Range:** Operating: 0°C ~ +50°C on full load; storage & shipping: -20°C ~ +80°C
- Humidity: 85% on operating, 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency:** Typical up to 85%
- **Rise time:** Less than 20ms
- **Hold-up Time:** 16 ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C

Dimensions (LxWxH): 240x100x70mm /9.4x3.9x 2.7 inch

Input Characteristics

Input Range: 90 ~ 264Vac, Full Range Input
Frequency: 47 ~ 63Hz
Input Current: Max 10A @ 115Vac, 5.0A @ 230Vac
Inrush Current: No Damage

Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	1.5A	12A	25A	± 5%	50mV P-P
+5V	1.0A	12A	25A	± 5%	50mV P-P
+12V1	1.0A	8.0A	16A	± 5%	120mV P-P
+12V2	1.0A	8.0A	16A	± 5%	120mV P-P
+12V3	1.0A	8.0A	16A	± 5%	120mV P-P
-12V	0.0A	0.25A	0.5A	± 10%	120mV P-P
+5Vsb	0.0A	1.5A	3.0A	± 5%	50mV P-P

*+3.3V and +5V total output not exceed 150W
* +12V1 and +12V2 , +12V3 total output not exceed 35A
* Total output for this subject power supply is 500W

Sparkle Power Inc.
Main Office
1000 Rock Avenue
San Jose, CA 95131
TEL: 408-519-8888
FAX: 408-519-9999
E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
17071 Green Drive
City of Industry, CA 91745
TEL: 626-839-7180
FAX: 626-839-3395