

TRG150 Series

150 WATTS - AC/DC GENERAL SINGLE OUTPUT


FEATURES

- Wide input voltage
- Continuous short circuit protection
- Over voltage protection
- Output voltage available from 12VDC to 48VDC
- High efficiency 85% typical
- Meets EN55022 Class "B", conducted emissions
- MEPS compliance (Efficiency Mark V pending)
- ROHS compliance
- Active PFC function

SPECIFICATIONS

INPUT	
Voltage range	90 to 264Vac
Frequency	47Hz to 63Hz
Inrush current	120A max @ 264Vac
Isolation	Input to Output 4,242Vdc
Leakage current	3.5mA max.
OUTPUT	
Output voltage	Factory preset, see table (not adjustable)
Voltage set-point	+/-2% (60% load)
Ripple and noise	2% p-p max
Short circuit protection	Continuous (Auto recovery)
Over voltage protection	Recycle AC input to Restart
Hold-up time	8ms typ @ 115Vac
Load regulation	+5% (20% to 160% load)
Line regulation	+/-1% max 100Vac to 240Vac at full load
ENVIRONMENTAL	
Operating temperature	0°C to +60°C
Load Derating	Derate from 100% at 40°C linearly to 60% at 60°C
Storage temperature	-20°C to +85°C

TECHNICAL ILLUSTRATION



STANDARDS AND APPROVALS	
Safety standards	Queensland Electrical Safety Office Certificate of approval Qld Q090086, AS/NZS 60950.1:203, EN60950
C-tick	AS/NZS CISPR 11:2002 Group 1
EMI standards	Meets EN55022 Class B and CISPR/FCC Class B
RCM	Complies with AS/NZS 4417 Parts 1,2,3 N911
MECHANICAL	
Dimensions	180 x 74 x 41mm
AC Inlet	IEC320/C14
Output connector	Right angle, hollow barrel connector, 2.5mm inside diameter; 5.5mm outside diameter; 9.5mm length Center positive polarity.
DC cord length	68AWG/UL2464

SELECTION TABLE

Consult Powerbox for variation of output connector and DC Cord Lengths

MODEL NUMBER	RATED VNOM	OUTPUTCURRENT	MAX POWER
TRG150A120 - 21E11	12Vdc	12.5A	150W
TRG150A150 - 21E11	15Vdc	10A	150W
TRG150A240 - 21E11	24Vdc	6.25A	150W
TRG150A480 - 21E11	48Vdc	3.13A	150W