Pushing Performance

# Han 16B-HBM double lever black



Image is for illustration purposes only. Please refer to product description.

| | |
|---|---|
| Part number | 09 30 716 0301 |
| Specification | Han 16B-HBM double lever black |
| HARTING eCatalogue | https://b2b.harting.com/09307160301 |

## Identification

| | |
|---|---|
| Category | Hoods/Housings |
| Series of hoods/housings | Han® B |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | Black |
| Type | Low construction |

## Version

| | |
|---|---|
| Locking type | Double locking lever |
| Han-Easy Lock® | Yes |
| Size | 16 B |
| Field of application | Standard hoods/housings for industrial connectors |

## Technical characteristics

| | |
|---|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4<br>4X<br>12 |

## Material properties

| | |
|---|---|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Pushing Performance

## Material properties

| | |
|---|---|
| Material (locking) | Polycarbonate (PC)<br>Stainless steel |
| Colour (locking) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |

## Specifications and approvals

| | |
|---|---|
| Approvals | DNV GL |
| CE | Yes |

## Commercial data

| | |
|---|---|
| Packaging size | 1 |
| Net weight | 120.4 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com