

Sealed Choke Coil SDER041B type

■ Features

Low profile : 4.0mm x 4.0mm x 1.2mm

Low coil resistance with large currents.


High magnetic shield construction should actualize high resolution for EMC protection.

100% lead (Pb) free meet RoHS standard

■ Application

Cellular phones, LCD displays, HDDs, DVCs, DSCs, PDAs etc..

■ Outline Dimensions




| Code | Dimensions (mm) |
|------|-----------------|
| L | 4.0 ± 0.2 |
| W | 4.0 ± 0.2 |
| T | 1.2 Max |

Note: This graph is in regard to outline dimensions spec. For outer appearance, please refer to actual product.

■ **Marking**


The inductor is marked with a 3-digit code

Example -- 10.0 μ H → 100



■ **Recommend Land Pattern Dimensions**

The customer shall determine the land dimensions shown below after confirming and safety.



| | |
|---|-----|
| A | 3.6 |
| B | 1.8 |
| C | 4.1 |

Unit : mm

■ Specifications

| Part Number | L0 Inductance (μH) @ (0A) | R_{dc} (m Ω) | | Heat Rating Current DC Amps. Idc (A) | | Saturation Current DC Amps. Isat (A) | |
|----------------|--|------------------------|---------|---|---------|---|---------|
| | | Typical | Maximum | Typical | Maximum | Typical | Maximum |
| SDER041B-R47MS | 0.47 | 28 | 33.6 | 3.90 | 3.50 | 4.25 | 3.60 |
| SDER041B-2R2MS | 2.2 | 69 | 83 | 2.70 | 2.43 | 2.00 | 1.80 |
| SDER041B-4R7MS | 4.7 | 109 | 131 | 1.90 | 1.71 | 1.45 | 1.30 |
| SDER041B-6R8MS | 6.8 | 130 | 156 | 1.70 | 1.53 | 1.20 | 1.08 |
| SDER041B-100MS | 10.0 | 190 | 228 | 1.45 | 1.30 | 1.10 | 1.00 |
| SDER041B-150MS | 15.0 | 339 | 407 | 1.05 | 0.95 | 0.80 | 0.72 |
| SDER041B-220MS | 22.0 | 410 | 492 | 0.95 | 0.855 | 0.70 | 0.63 |
| SDER041B-470MS | 47.0 | 850 | 1,020 | 0.50 | 0.45 | 0.46 | 0.41 |

* : If you require another part number please contact with us.

** : Inductance Tolerance $\pm 20\%$

Note 1. : All test data is referenced to 25°C ambient.

Note 2. : Test Condition;100KHz, 1.0Vrms

Note 3. : Idc : DC current (A) that will cause an approximate ΔT of 40°C

Note 4. : Isat : DC current (A) that will cause L0 to drop approximately 30%

Note 5. : Operating Temperature Range -55°C to + 125°C

Note 6. : The part temperature (ambient + temp rise) should not exceed 125°C under the worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Note 7. : The rated current as listed is either the saturation current or the heating current depending on which value is lower.

Current Characteristic

