


SD

SD



NOTES:

1. FOR USE WITH RG-58, 58A, 58C & 141/U CABLES.
2. FOR CABLING TRIMMING USE KTJ-75 & KTD-110.
3. FOR CRIMPING USE DIE SIZE 86.
4. FOR CABLING INSTRUCTIONS SEE CP-429.
5. MARK PACKAGE: KINGS KO-59-02, YRWK(DATE CODE)
6. MATERIALS:
 - GASKET: SILICONE RUBBER, ZZ-R-765
 - INSULATOR: TEFLON, ASTM-D-4894
 - SPRING: STAINLESS STEEL WIRE
 - OUTER CONTACT: BERYLLIUM COPPER, ASTM-B-196
 - ALL OTHER PARTS: BRASS, ASTM-B16
7. FINISHES:
 - CENTER CONTACT: GOLD PLATE PER, MIL-G-45204
 - ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
8. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHM.
 - FREQUENCY RANGE: DC TO 10 GHz
 - WORKING VOLTAGE: 500 VOLTS RMS

REVISIONS

ISSUE	CHANGES
5	CN 37546 C REDRAWN JW 03/12/98

K0-59-02

K05902S

SCALE 4:1

APPROX SURFACE AREA

USED ON

REF: BOEING

PLUG, TPS

DRAWN	HFE	DATE	06/21/68
DESIGN	PETE	DATE	06/26/68
APPR.		DATE	

KINGS
ELECTRONICS CO., INC.
TUCKAHOE, NEW YORK 10707

K0-59-02