


Sales Region	Worldwide (except Japan)
Series	PXA
Model	PXA15
Status	 Production
Option	Negative logic ON/OFF control Trim - remote adjust
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	



Electrical Characteristics

Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	18 to 36Vdc
Efficiency	87% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	10.8 to 13.2Vdc
Output Current Range	0 to 1.25A
Maximum Ripple Noise	100mV
Maximum Output Power	15W
Withstanding Voltage1	Input - Output: 2250DC: 1min.
Withstanding Voltage2	
Withstanding Voltage3	

Package Type & Size

Package / Mounting	PCB mount
Width(W)	27.9mm Nom. (1.10in Nom.)
Height(H)	8.5mm Nom. (0.33in Nom.)
Depth(D)	23.9mm Nom. (0.94in Nom.)
Weight	
Industry Standard Size	1x1 inch size
Terminal Style	DIP

Other

Operating Temp. Range	-40 to 85°C
Isolation	Isolated
Feature	
Safety Standard(Certified)	IEC60950-1 EN60950-1 UL60950-1

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Safety Standard(Conformed)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
