


GaAs PIN photodiode array

G8921-01

Photodiode array for data communication



Features

- Active area: $\phi 0.06$ mm
Element pitch: 250 μ m
4-element array
- High-speed response: 10 Gbps [(2.5 Gbps per channel) $\times 4$]
at low bias voltage ($V_R=2$ V)
- Low dark current, low capacitance
- Up to 16 elements available as option

Applications

- Optical fiber communications
- High-speed data link

General ratings

Parameter	Symbol	Value	Unit
Active area	-	$\phi 0.06$	mm
Element pitch	-	250	μ m
Number of elements	-	4	ch

Absolute maximum ratings


Parameter	Symbol	Remark	Value	Unit
Reverse voltage	V_R Max.		30	V
Reverse current	I_R Max.		0.5	mA
Operating temperature	T_{opr}	*	-40 to +85	$^{\circ}$ C
Storage temperature	T_{stg}		-55 to +125	$^{\circ}$ C

* In N₂ environment or in vacuum

Electrical and optical characteristics (Unless other wise, $T_a=25$ $^{\circ}$ C, per 1 element)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	470 to 870	-	nm
Peak sensitivity wavelength	λ_p		-	850	-	nm
Photo sensitivity	S	$\lambda=850$ nm	0.45	0.5	-	A/W
Dark current	I_D	$V_R=5$ V	-	2	50	pA
Terminal capacitance	C_t	$V_R=2$ V, $f=1$ MHz	-	0.35	0.5	pF
Cut-off frequency	f_c	$\lambda=850$ nm, $V_R=2$ V, $R_L=50$ Ω , -3 dB	2	-	-	GHz

■ Spectral response




KGPD80048EA

■ Dark current vs. reverse voltage




KGPD80049EA

■ Terminal capacitance vs. reverse voltage




KGPD80050EA

■ Cross-talk characteristic



KGPD80051EA

■ Dimensional outline (unit: mm)



KGPD80017EA

HAMAMATSU

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2002 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741