ISO 9001 : 2000 TÜV CERT Cert.No.:0410020138

SPECIFICATION

PART NO. 101110FD0V7M442ZA

DESCRIPTION. RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

CUSTOMER. _____

REV. : PA **REV. DATE : 2006 / Aug / 30**

	APPROVED	CHECKED	PREPARED
NAME	Kenny Chen	Bryant Tu	Nicole Lee

實盈股份有限公司

SUYIN CORPORATION

TAIWAN HEAD OFFICE :
NO. 377.Fu-The First Re., His-Chih,
Taipei Hsien, Taiwan, R.O.C.
TEL：(886) 2-2694-7697 (Rep)
FAX：(886) 2-2694-8407 2694-8047
E-mail：Lesley@suyin.com.tw

SUYIN ELECTRONICS (DONGGUAN) CO., LTD.
Suyin Road, San Zhong,
Qing XI Town, Dongguan City,
TEL：(886) 2-2694-7697 (Rep)
FAX：(886) 2-2694-8407 2694-8047
E-mail：kevin@suyin.com.tw

HONG KONG BRANCH OFFICE :
TEL：(852) 2-559-6017
FAX：(852) 2-5596461
E-mail：suyin@netvigtor.com

KOREA BRANCH OFFICE :
TEL：(82) 2-559-6017
FAX：(82) 2-5596461
E-mail：yang@sdint.co.kr

GERMANY BRANCH OFFICE :
TEL：(+49) 0-8561/238-8880
FAX：(+49) 0-8561/238/8888
E-mail：mail@suyin.de

JAPAN BRANCH OFFICE :
TEL：(81) 45-266-2488
FAX：(81) 45-266-2489
E-mail：kanashiro@suyinjapan.com

SINGAPOER BRANCH OFFICE :
90 Lorong 23 Geylang #02-01/02/03 Yong
DA Industrial Building Singapore 388393
TEL：(65) 6256-6481
FAX：(65) 6256-6483
E-mail：alice@suyin.com.sg

U.S.A BRANCH OFFICE :
TEL：(1) 714-750-0378
FAX：(1) 714-750-0379
E-mail：steven@suyinusa.com

ISRAEL BRANCH OFFICE :
TEL：(1) 714-750-0378
FAX：(1) 714-750-0379
E-mail：sales@suyin.co.il

SUYIN CORPORATION
SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

1 P/N SPECIFICATION

SUYIN P/N: **101 110 F** **D** **0V** **7** **M4** **42** **ZA**
A B C D E

A. Transformer Speed: 10/100 Base-T
LED Polarity: Reverse

B. Schematic: Refers to section 5.1

C. LED Color Code:

w/o LED: 0		RIGHT LED					
		YELLOW	GREEN	ORANGE	G/O	G/Y	O/G
LEFT LED	YELLOW	1	7	D	K	N	R
	GREEN	2	8	E	L	P	S
	ORANGE	3	9	F	M	Q	T
	G/O	4	A	G			
	G/Y	5	B	H			
	O/G	6	C	J			

D. RJ Contact Plating:

M2: Gold Flash selected Gold plating over 50 u" min. Nickel
M3: 10u" selected Gold plating over 50 u" min. Nickel
M4: 15u" selected Gold plating over 50 u" min. Nickel
M5: 30u" selected Gold plating over 50 u" min. Nickel
M6: 50u" selected Gold plating over 50 u" min. Nickel.

E. Mechanical Series: Refers to section 2.1~2.2


SUYIN CORPORATION

SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

2 MECHANICAL DIMENSIONS

2-1 Dimensions




General Tolerance : 0~10mm: ±0.10
10~30mm: ±0.13
30~ mm: ±0.30

SUYIN CORPORATION

SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

2-2 PCB Layout




RECOMMENDED PCB LAYOUT
COMPONENT SIDE
ALL DIMENSION TOLERANCE ARE ±0.05mm

SUYIN CORPORATION


SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER


3 RECOMMEND RJ PLUG SPECIFICATION



* There must be no damage to housing or locking latch.There must be no nicks or cuts in cable.
* Durability : 750 cycles generally



FOLLOW SPECIFICATION : FCC, PART 68, SUBPART F FIGURE 68.500 (C)(2)(ii)



FOLLOW SPECIFICATION : FCC, PART 68, SUBPART F FIGURE 68.500 (C)(2)(i) AND IEC 603-7 FIGURE 23 & 24

SUYIN CORPORATION
SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

4 MATERIAL SPECIFICATION

4-1 RoHS Compliance per EU Directive 2002/95/EC

4-2 Plastic Housings:

A. Housings: Nylon9T, UL 94V-0, Black

4-3 Terminals:

A. RJ Contacts: Phosphor Bronze
B. RJ Solder Pins: Brass
C. LED Solder Pins: Brass
D. Transformer Housing Solder Pins: Brass

4-4 Shields:

A. Shield: Stainless Steel

4-5 Plating:

A. RJ Contacts: As P/N specified
B. RJ Solder Pins: 100u" min. Matte Tin over 50u" Nickel under-plating
C. LED Solder Pins: 100u" min. Tin over 50u" Nickel under-plating
D. Transformer Housing Solder Pins: 100u" min. Matte Tin over 50u" Nickel under-plating
E. Shield Grounding Legs: Pre-soldering, Sn/ Ag/ Cu (96.5/ 3/ 0.5)

4-6 PCB: FR-4, Two Layer PCB


4-7 Internal Solder Joints: Sn/ Ag/ Cu (96.5/ 3/ 0.5)


SUYIN CORPORATION
SPECIFICATION


DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

5 ELECTRICAL CHARACTERISTICS

5-1 Schematic







5-2 Transmitter & Receiver Filter:

Insertion Loss (dB MAX)	Return Loss at 100Ω (dB MIN)		
1~100MHz	1~30MHz	30~60MHz	60~80MHz
-1.0	-18	-16	-12

5-3 Common Mode Rejection @ 1~100 MHz: -30dB MIN

5-4 Cross Talk @ 1~100 MHz: -35dB MIN

5-5 Inductance @ 100KHz/ 0.1V, 8mA DC BIAS: 350μH MIN

5-6 HiPot Test: 1500Vrms, 60sec

5-7 LED:

Forward Voltage (V) @ 20mA	
Typical	MAX
2.2	2.6

6 OPERATING & TEST REQUIRMENTS

Product is designed to meet electrical, mechanical and environmental performance requirements specified below. All tests are performed at ambient environmental conditions per MIL-STD-1344A and EIA-364 unless otherwise specified

6-1 Operating Temperature Range: 0℃ TO +70℃

6-2 Storage Temperature: -40℃ to 85℃

6-3 Ratings:

1. Insulation Resistance: 500M Ohm (MIN)
2. Dielectric Withstanding Voltage: 1000 VAC


SUYIN CORPORATION
SPECIFICATION

DOCUMENT NO.: 101110FD0V7M442ZA SUYIN P/N. : 101110FD0V7M442ZA CUSTOMER P/N. :	DESC. : RJ45 1X1 TAB DOWN W/LED & TRANSFORMER

7 STORAGE REQUIRMENTS

All products shall be packaged against any physical damage and corrosion during shipment or in storage.

8 RECOMMEND WAVE SOLDERING PROFILE



PARAMETER	REFERENCE	LEAD FREE SPECIFICATION
PREHEAT TEMPERATURE GRADIENT		+1~4℃/sec
PREHEAT TIME	t1	2~3 MIN
PREHEAT TEMPERATURE	T1	>100℃
SOLDER POT TEMPERATURE	T PEAK	260℃±5℃
DWELL TIME	t2	3.5 SEC
PEAK BOARD TOP TEMPERATURE		190℃
COOLING TEMPERATURE GRADIENT		-6℃/SEC MAX.