

This document was generated on 10/08/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 43640-0208

Status: Active

Overview: Micro-Fit 3.0™ Connectors

Description: Micro-Fit 3.0™ Plug Housing, Single Row, with Panel Mount Ears, 2 Circuits, Glow

Wire Compatible

Documents:

3D Model Test Summary TS-43045-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-43650 (PDF) Product Literature (PDF)

Packaging Specification PK-43640-003 (PDF)

Agency Certification

CSA LR19980 TUV R72081037 UL E29179

General

Product Family Crimp Housings

Series <u>43640</u>

Application Power, Wire-to-Wire Comments This Molex product is

This Molex product is manufactured from material that has the following ratings, tested by independent agencies :. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety; section 30 Resistance to heat and fire.<P><P>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s).<P>If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options.


Overview Micro-Fit 3.0™ Connectors

Product Literature Order No 987650-5984
Product Name Micro-Fit 3.0™

UPC 883906114350

Physical

2 Circuits (maximum) Color - Resin Black Flammability 94V-0 Gender Male Glow-Wire Compliant Yes Keying to Mating Part None Lock to Mating Part Yes Material - Resin Nylon Net Weight 0.391/qNumber of Rows Packaging Type Bag



EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status

Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

43640 Series

Mates With

43645 Micro-Fit 3.0™ Receptacle Housings

Use With

43031 Micro-Fit 3.0™ Male Crimp Terminals

Panel Mount Yes
Pitch - Mating Interface 3.00mm
Polarized to Mating Part No
Stackable No

Temperature Range - Operating -40°C to +105°C

Electrical

Current - Maximum per Contact 5A

Material Info

Reference - Drawing Numbers

Packaging Specification PK-43640-003
Product Specification PS-43650
Sales Drawing SD-43640-001
Test Summary TS-43045-001

This document was generated on 10/08/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION