MURS205-MURS260

塑封外延快恢复整流二极管


反向电压 50 ~ 600 V

正向电流 2.0 A

Plastic Epitaxial Fast Recovery Rectifiers

Reverse Voltage 50 ~ 600 V

Forward Current 2.0 A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力强 High forward surge capability
- 高信赖性 High reliability
- 高温焊接保证 High temperature soldering guaranteed:
  260℃/10 秒, 引线长度:0.375" (9.5mm)
  260℃/10seconds,9.5mm lead length
- 引线和管体皆符合RoHS标准
  Lead and body according with RoHS standard
- 型号后缀"-F"标记无卤素产品
  Green compound with suffix "-F" on Marking

机械数据 Mechanical Data

- 封装外形:DO214AA 塑封 Case:DO214AA Molded plastic
- 环氧树脂：UL易燃等级：94V-0
  Epoxy: UL 94V-0 rate flame retardant
- 引脚：镀锡,无铅 Lead: Pure tin plated, lead free

最大值和特性 TA = 25℃ 除非另有规定。

Maximum Ratings & Characteristics Ratings at 25℃ ambient temperature unless otherwise specified.

参数 Parameter	符号 Symbols	MURS 205	MURS 210	MURS 220	MURS 240	MURS 260	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	V
最大均方根电压 Maximum RMS voltage	V_{RMS}	35	70	140	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	$I_{F(AV)}$	2.0					A
正向不重复浪涌电流 8.3 ms单一正弦半波 Non-repetitive peak forward surge current 8.3 ms singlehalf sine-wave	I_{FSM}	50					A
最大正向电压 @IF=2.0A Maximum forward voltage	V_F	0.940			1.25		V
最大反向电流 @V_{DC} TA= 25℃	I_R	5					μA
Maximum reverse current TA= 125℃		100					
最大反向恢复时间 IF=0.5A , IR=1.0A ,IRR=0.25A MAX. reverse recovery time	Trr	20			50		nS
典型热阻 Typical thermal resistance (Note 1)	RθJA	25					℃/W
典型结电容 VR=4.0V,f=1MHz Type junction capacitance	Cj	105			90		pF
工作结温和存储温度 Operating junction and storage temperature rang	Tj, TSTG	-55 --- +150					℃


备注 Note:

1) 引线长度 0.375" (9.5 mm)，安装在PCB板上，从PN结到周围环境的热阻。

1) Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length, PCB mounted.


正向特性曲线（典型值）

TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线


FORWARD CURRENT DERATING CURVE



浪涌特性曲线（最大值）


MAXIMUM NON REPETITIVE

PEAK FORWARD SURGE CURRENT



反向特性曲线

Typical Reverse Characteristics



Shanghai Leiditech Electronic Co.,Ltd
Email: sale1@leiditech.com
Tel : +86- 021 50828806
Fax : +86- 021 50477059