General Cable Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C4014A Revision Level: 1 Date: 11/21/2007

3P 22 SOLID TC SR-PVC PVC **COMMUNICATION CABLE**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#22 AWG Solid Tinned Copper	0.025" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.046" nom.
Pairing	6 conductors into 3 pairs @ 2.00" LHL.	0.092" nom.
Cable:	3 pairs @ 3.00" LHL with polyester binder	0.165" nom.
Jacket:	0.032" Wall Polyvinyl Chloride - Gray	0.229" +/- 0.011"
Print Legend:	***CAROL (R) 22 AWG Solid***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	16.7 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	24.5 pF/ft @ 1kHz nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	P1=Black, Red
2	P2=Black, White
3	P3=Black, Green

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.