


P6187W

18.5" WXGA TFT Widescreen Industrial LCD Monitor

Features

- 18.5" WXGA TFT LED backlight LCD
- NEMA 4/12 (IP65)- compliant panel mounting flat panel monitor
- Supports panel mount, wall mount and VESA mount
- Multi-touch 18.5" projective capacitive
- Full range screw-type (locked) AC-in or 24V DC-in (option)
- VGA, S-video, Video and DVI with multi-signal inputs



▲ Modularized design



- | | |
|-----------------|-------------------------|
| 1. Exit | 7. DC power input |
| 2. Menu | 8. T/S port |
| 3. SEL- | 9. DVI (Only for DVI-D) |
| 4. SEL+ | 10. VGA |
| 5. Power LED | 11. Video (CVBS) |
| 6. Power switch | 12. S-video |

Introduction

The P6187W is a slim and flat front bezel design industrial LCD monitor, which adopts 18.5-inch 300 nits WXGA LCD display and supports multi-signal interfaces including DVI, VGA, S-Video, Video. Featuring NEMA 4/12 & IP65 compliant front bezel, screw-type adaptor plug design, and 12/24V DC-In means it is fit for all kinds of industrial environments. Moreover, the P6187W supports panel mount, wall mount or VESA FPMPI (Video Electronics Standards Association Flat Panel Monitor Physical Mounting Interface) mounting. With the compact mechanism design, users can enjoy free from space constraint. It is especially suitable for POI/POS, excellent HMI and all kinds of heavy-duty industrial fields.

Specifications

Front Bezel	NEMA 4/12 (IP65)-compliant, plat front bezel	
Mounting	Panel mount, wall mount and VESA arm FPMPI mounting (video electronics standards association flat panel monitor physical mounting interface)	
LCD Panel	Display	18.5" WXGA TFT LCD
	Max. Resolution	1366 x 768
	Max. Colors	16.7M
	Active Area (mm)	409.8 x 230.4
	Pixel Pitch (mm)	0.3 x 0.3
	Response Time	5ms
	Backlight	LED
	Backlight MTBF	50,000 hrs
	Viewing Angle (H/V)	170°/160°
	Contrast Ratio	1000 (TYP.)
	Brightness (cd/m ²)	300 nits
Display Control	OSD (on screen display)	
Display Mode	VGA 640 x 350 (70Hz), VGA 640 x 480 (60/72/75Hz), VGA 720 x 400 (70Hz), SXGA 800 x 600 (60/72/75Hz), XGA 1024 x 768 (60/72/75Hz), WXGA 1366 x 768 (60Hz)	

Specifications

Input Signal	VGA Video: R.G.B Analog 0.7v Peak-to-Peak Video S-video DVI (Oly for DVI-D) Touchscreen: USB interface
I/O Connectors	1 x USB for touchscreen version 1 x VGA input 1 x RCA for video 1 x S-video for video 1 x DVI 1 x Screw-type DC power input
Power Adapter	Screw-type external AC/DC power adapter
Power Consumption	22 W
Touchscreen	Multi-touch 18.5" projective capacitive
Dimensions	460 mm (18.11") (W) x 57 mm (2.44") (D) x 285 mm (11.22") (H)
Packing Dimensions	595 mm (24.43") (W) x 190 mm (7.48") (D) x 490 mm (19.29") (H)
Weight (net/gross)	6.0 kg (12.22 lb)/ 8.0 kg (17.75 lb)
Environment	Operating temperature: 0°C ~ +55°C (+32°F ~ +131°F) Relative humidity: 20%~90% @ 40°C, non-condensing
Certificate	CE

Ordering Information

P6187W		
AC Power	Panel Mount Monitor	
	Capacitive (USB)	P6187WPC-AC-U-US-EU
	Glass	P6187WPG-AC-US-EU
24VDC Power	Panel Mount Monitor	
	Capacitive (USB)	P6187WPC-24VDC-U
	Glass	P6187WPG-24VDC

Dimensions

