



## ZWS15B-5





Sales Region	Worldwide
Series	ZWS-B
Status	Production
Feature	
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	78% Typ.	
Rated Output Voltage[DC]	5V	
Output Voltage Range[DC]	4.5 to 5.5V	
Maximum Output Current	3A	
Maximum Output Power	15W	

Cases Shape & Size		
Case' shape	PC board	
Width(W)	50mm Nom.	
Height(H)	22mm Nom.	
Depth(D)	87.5mm Nom.	
Weight	55g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Convection cooling	
	UL60950-1	
Cafaby Standard (Cartified)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	Den-an	
	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

<sup>!</sup> Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.