




ChanneLED 5

High output red solution

ChanneLED 5 LED lighting system offers simplicity and flexibility while providing bright, vivid and uniform illumination for face-lit channel letters, sign cabinets, cove lighting and an endless array of low-voltage applications.

- Run 45 feet per SloanLED 60 W 12 VDC power supply
- SloanStretch expandable wire (+2 in) feature for optimum module placement
- Constant Current Technology (CCT)



Specifications

| | | |
|---------------------------------|--|-----------------|
| Part number | 701269-R5-MB | |
| Dimensions L x W x H | 4 in x 0.46 in x 0.45 in | |
| Viewing angle | 120° | |
| LEDs per module | 3 | |
| Modules per foot | 2 | |
| Maximum coverage per row | Can depth | Coverage |
| | ≥5 in | 7.5 in |
| Operating temperature | -40° C to +70° C | |
| Protection class | IP66 | |
| Special feature | SloanStretch expandable wire (+2 in) | |
| Power per module | 0.60 W | |
| Efficacy | 30 lm/W | |
| Power capacity | 90 modules per SloanLED 60 W 12 VDC power supply | |
| Fastening | Peel-n-stick and mechanical | |
| Packaging | 25 ft (50 modules) per tray, 5 trays per carton | |
| Color | Red | |
| Lumens per module | 18 | |

