



CHENMKO ENTERPRISE CO.,LTD

Lead free devices

SURFACE MOUNT

SCHOTTKY BARRIER DIODE

VOLTAGE 40 Volts CURRENT 0.5 Ampere

CH411N1PT

APPLICATION

* Low power rectification


FEATURE

- * Small surface mounting type. (FBPT-923)
- * Low VF. (VF=0.43V Typ. at 0.5A)
- * High reliability


CONSTRUCTION

* Silicon epitaxial planar

CIRCUIT



FBPT-923



Dimensions in millimeters

FBPT-923

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CH411N1PT	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	40	Volts
Maximum RMS Voltage	VRMS	28	Volts
Maximum DC Blocking Voltage	VDC	20	Volts
Maximum Average Forward Rectified Current	IO	0.5	Amps
Peak Forward Surge Current at 8.3 mSec single half sine-wave	IFSM	3.0	Amps
Typical Junction Capacitance between Terminal (Note 1)	CJ	20	pF
Maximum Operating Temperature Range	TJ	+125	°C
Storage Temperature Range	TSTG	-40 to +125	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CH411N1PT	UNITS
Maximum Instantaneous Forward Voltage at IF(1)= 10mA	VF(1)	0.30	Volts
Maximum Instantaneous Forward Voltage at IF(2)= 500mA	VF(2)	0.50	Volts
Maximum Average Reverse Current at VR= 10V	IR	30	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 10.0 volts.
2. ESD sensitive product handling required.

2006-07

RATING CHARACTERISTIC CURVES (CH411N1PT)

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL JUNCTION CAPACITANCE

