



NOTES:
 1. FOR USE WITH RG-58, 58A, 58C, 141 & 141A/U CABLE
 2. FOR CABLE TRIMMING USE KTY-113 & KTD-166.
 3. FOR FORMING USE CRIMP DIE SIZE 01.
 4. FOR CABLING INSTRUCTIONS SEE CP-465.

UNLESS OTHERWISE SPECIFIED:
 1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
 3 PLACE DECIMALS ± .004 ANGLES ± 0° 30'
 T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED HALF THE SUM OF THEIR TOLERANCES.
 2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
 3. NO FILLETS PERMITTED.
 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
 5. ALL DIMENSIONS PRIOR TO PLATING.

ITEM	REQ'D	DESCRIPTION	DRAWING NO.
9	1	CABLING INSTRUCTIONS	3-167-2M88
8	1	TNC CRIMP CAPTIVE CONTACT F	1-521-27M9D
7	1	INSULATOR	
6	1	RETAINING RING	
5	1	HEX NUT	492A-9-MC7
4	1	LOCKWASHER	492A-12-MC7
3	1	GASKET	492A-10-M99
2	1	K-GRIP BODY	
1	1	K-GRIP SLEEVE	N-59-29-2-MC7

M39012/28-0010 S-D

REVISIONS	
ISSUE	CHANGES
0	ER 11221 WLA 14 JUN 72
1	CN 12413A ME 11 JUL 73
2	CN 12884A J.G.L. 30 OCT 73
3	CN 21741C M.A. 12 MAR 81
4	CN 22767 E. JEP 16 NOV 81
5	CN 32302 A LNM 20 JUN 90

S-D

KA-19-101

REF.

FINISH

SPEC. KER-10004

MATL.

SPEC.

TNC
BULKHEAD JACK

DRAWN WLA. DATE 12 JUN 72

APPR. LI DATE 14 JUN 72

KINGS ELECTRONICS
40 HARLEDALE ROAD
TUCKAHOE, N. Y. 10707

M39012/28-0010