



Main

Product or component type	Communication card
---------------------------	--------------------

Complementary

Range compatibility	Altivar 32 Lexium 32 Altivar Process Altivar Easy 610
Communication port protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission rate	9.6 kbps...12 Mbps
Addressing	Configuration settings 1...126 configurable by graphic terminal/SoMove software
Communication service	Drive profile native ATV32 conforming to IEC 61800-7-201 (CiA 402) Several DP V1 messaging modes Parameters management compliant with PROFIdrive V4.1 Mapping of the process data from the master 4 configurable telegrams
Display type	1 LED for bus fault (BF) 1 LED for RUN
Diagnostic function	Diagnostic data with VSD status Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests
Bus profile	CiA 402 PROFIdrive
Standards	IEC 61800-7-201 (CiA 402)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0936 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual