




Pluggable PCB Connectors

GSK 760/ 2

Female Header, Pin Spacing: 3.5 mm, 2 pole, Voltage Rating: 125 V, Current Rating: 8 A, Cross-Section: 1.5 mm², Connection Type: Screw



Order Info

Reference Number (ref. no.)	362002
Applications	Lighting, Electrical Appliances, Electronics
PU	500
EAN	4028012109937

Type

Type	Female Header
Number of poles	2 pole
Clamping Units per Pole	1
Colour	blue
Cross-Section	1.5 mm ²
Connection Type	Screw
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	125 V
Current Rating	8 A
Insulating Material	PBT
Contact Material	Brass
Core Cross-Section min.	0.5 mm ²
Core Cross-Section max.	1.5 mm ²
Flammability Rating	V-0
max. Ambient Temperature Operation	60 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0-6.5 mm
Assembly Contact Screw	0.4x2.5 / \cup 0.2 Nm
Pin Spacing	3.5 mm
Approbation EN61984	GSK760_GST760_GSK_864_GSK864_EN61984_20060227_2011051:
Approbation UL	GSK760_GSK860_GSK864_GSK865_UL_E63492_1-11_Description_v
Approbation CSA	GSK_GST_Printklemmen_Serie_20160404_CSA_70070893_Certificat