



Main

Product or component type	Circuit breaker
Range of product	PowerPact P
Current sensor rating range	800 A
Line Rated Current	800 A
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)3
Trip unit technology	Electronic, power, Micrologic 6.0 P, LSIG

Complementary

Product certifications	IEC UL Listed CSA
[Ue] rated operational voltage	600 V AC
Module type	P-Frame
Mounting location	Bolt-on
Mounting mode	Unit mount
Poles description	3P
Breaking capacity code	J
Electrical connection	Lugs line Terminal nut load
Continuous current rating	80 %
Device short name	B
Communication interface	Modbus
Maximum Height	12.86 in (326.64 mm)
Maximum Depth	8.05 in (204.47 mm)
Maximum Width	8.27 in (210.06 mm)

Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m)
-------------------	--

Ordering and shipping details

Category	01215-PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes