


VAR-18078077M3S-K



| | |
|----------------------------|---|
| Series | VAR-18 |
| Type | Side Electrode |
| Number of Electrode | 3 |
| Status | Production (Not Recommended for New Design) |



| Size | |
|---------------------|----------------|
| Outer Diameter(ΦD1) | 7.80mm ±0.20mm |
| Inner Diameter(ΦD2) | 5.35mm ±0.20mm |
| Thickness(T) | 0.65mm Max. |

| Electrical Characteristics | |
|---|-------------|
| Reference Current | 10mA |
| Varistor Voltage | 5.9 to 9.4V |
| Non Linear Coefficient [1 to 10mA] | 2.3 |
| Temperature Coefficient of Varistor Voltage | ±0.3%/°C |
| Capacitance (Min.) [1kHz] | 1nF |
| Capacitance (Max.) [1kHz] | 50nF |
| Rated Power | 300mW |

| Other | |
|-----------------------------|------------------------|
| Operating Temperature Range | -25 to 85°C |
| Packing | Bulk(Polystyrene form) |
| Package Quantity | 5000pcs |
| Weight | 0.0662g |

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.



Associated Images

