



P. C. B LAYOUT

规格:

1. 插入力: 44.1N MAX.
2. 拔出力: 7~25N
3. 耐久性: 10000 CYCLES MIN.
4. 额定电流: 0.5A
5. 额定电压: 40V MAX
6. 耐电压: 500V AC MIN. (UNMATED)
300V AC MIN. (MATED)
7. 接触阻抗: 30mΩ MAX.
8. 绝缘电阻: 100MΩ MIN (UNMATED)
10MΩ MIN (MATED)
9. 工作温度: -20℃ TO +85℃
10. 所用材质须符合RoHS要求

外壳镀金:
HXC12-HDMI A19-610A



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: HDMI A TYPE 三排插件	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HXC12-HDMI19-610B	MOLD NO. /
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY:	DATE : 2014-02-23	DRAW NO: HXC-HDMI13091102	SHEET NO. 1 OF 1