



SPECIFICATION
 Contact Rating : 50mA,12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min.500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 0.15mm
 Operating Temp : -30℃~+85℃
 Storage Temp : -30℃~+80℃

A:With B:without

| | |
|-----------------|-------------------------|
| PAPT NO | TS-1010-X-X |
| Operating Force | A:100gf B:160gf C:260gf |
| Height | H: 3.5 |
| Fixed column | A:With B:without |

| | | | | | | |
|------|-----------|--------|-----|---------------|-------------------|--------|
| ⑤ | Terminal | — | 2 | Brass (0.30t) | Plating silvering | — |
| ④ | Contact | — | 1 | F.ag/Sus | Natural | — |
| ③ | Base | — | 1 | Lcp | | — |
| ② | Cover | — | 1 | Brass | Plating Nickel | — |
| ① | Keystake | — | 1 | Pa46 | | — |
| ITEM | PAPT NAMF | TER.NO | QTY | MATERIAL | FINISHING | REMARK |

| | | | | | | | | | | | | | |
|---|-------------|------|---------|----------|------------------------|---|--|------|--|------------|-----------------------------------|-------|----------|
| | | | | | units: mm | DSND | | DATE | | SCALE: N/A | MODEL TYPE: TACT SWITCH | | |
| | | | | | tolerance: | DWN | | DATE | | VIEW: | PART NO.: | | |
| △X | | | | | X.X ±0.2mm | CHKD | | DATE | | UNIT: mm | DWG NO.: | | |
| △X | | | | | X.XX ±0.1mm | APPD | | DATE | | SIZE: A4 | TS-1010-X-X | | |
| △X | | | | | X.XXX ±0.05mm | KKB INDUSTRIAL PRECISION CO.,LIMITED | | | | | WEIGHT | SHEET | REVISION |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES | | | | | | 1.0g | 1/1 | A0 |
| REVISIONS | | | | | | | | | | | | | |
| www.xk-dg.cn www.hellokcb.com www.hellokcb.cn | | | | | | | | | | | | | |