

Inductors

Commercial, Molded, Shielded, Miniature



FEATURES

- Flame retardant coating
- Electromagnetic shield
- Small package for a shielded inductor
- Epoxy molded construction provides superior moisture protection
- Precision performance, excellent reliability, sturdy construction



RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: ± 10 % standard. ± 5 % available
Insulation Resistance: 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

Dielectric Withstanding Voltage: 200 VAC per MIL-STD-202, Method 301 (sea level).

Percent Coupling: 3 % maximum per MIL-PRF-15305
Operating Temperature Range: - 55 °C to + 105 °C

STANDARD ELECTRICAL SPECIFICATIONS							
IND. (µH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF- [*] RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED ^{**} DC CURRENT (mA)	INCREMENTAL ^{***} CURRENT
0.10	± 10 %	54	25.0	490.0	0.10	670	-
0.12	± 10 %	52	25.0	430.0	0.11	635	-
0.15	± 10 %	50	25.0	415.0	0.12	610	-
0.18	± 10 %	49	25.0	375.0	0.13	585	-
0.22	± 10 %	47	25.0	330.0	0.15	545	-
0.27	± 10 %	46	25.0	300.0	0.16	530	-
0.33	± 10 %	44	25.0	260.0	0.18	495	-
0.39	± 10 %	42	25.0	230.0	0.19	485	-
0.47	± 10 %	41	25.0	220.0	0.21	460	-
0.56	± 10 %	41	25.0	210.0	0.23	440	-
0.68	± 10 %	39	25.0	180.0	0.24	430	-
0.82	± 10 %	38	25.0	165.0	0.27	405	-
1.0	± 10 %	37	25.0	150.0	0.30	385	-
1.2	± 10 %	40	7.9	130.0	0.73	247	-
1.5	± 10 %	41	7.9	115.0	0.86	228	-
1.8	± 10 %	43	7.9	105.0	0.95	217	-
2.2	± 10 %	45	7.9	95.0	1.1	202	-
2.7	± 10 %	48	7.9	90.0	1.2	193	-
3.3	± 10 %	49	7.9	80.0	1.3	185	-
3.9	± 10 %	50	7.9	75.0	1.5	173	-
4.7	± 10 %	53	7.9	70.0	2.4	136	-
5.6	± 10 %	54	7.9	60.0	2.9	124	-
6.8	± 10 %	55	7.9	55.0	3.2	118	-
8.2	± 10 %	55	7.9	53.0	3.6	111	-
10.0	± 10 %	57	7.9	50.0	4.0	106	-
12.0	± 10 %	36	2.5	35.0	3.0	122	-
15.0	± 10 %	38	2.5	30.0	3.4	115	-
18.0	± 10 %	40	2.5	26.0	3.8	108	-
22.0	± 10 %	40	2.5	24.0	4.9	96	-
27.0	± 10 %	40	2.5	21.0	5.8	88	-
33.0	± 10 %	41	2.5	20.0	6.5	83	-
39.0	± 10 %	42	2.5	19.0	7.9	75	-
47.0	± 10 %	44	2.5	16.0	9.3	69	-
56.0	± 10 %	44	2.5	15.0	11.0	64	-
68.0	± 10 %	45	2.5	13.0	12.0	61	-
82.0	± 10 %	45	2.5	11.0	13.0	59	-
100.0	± 10 %	40	2.5	10.5	16.8	51	-
120.0	± 10 %	31	0.79	13.0	5.8	88	27
150.0	± 10 %	33	0.79	12.0	7.9	75	24
180.0	± 10 %	33	0.79	11.0	9.4	69	22
220.0	± 10 %	35	0.79	10.0	11.0	64	20
270.0	± 10 %	37	0.79	9.0	12.0	61	18
330.0	± 10 %	40	0.79	8.0	16.0	53	16
390.0	± 10 %	38	0.79	7.8	21.0	46	14
470.0	± 10 %	36	0.79	7.5	24.0	43	13
560.0	± 10 %	36	0.79	7.0	28.0	40	12

* Measured with full length lead. ** **Rated DC Current:** Based on the maximum temperature rise not to exceed 15 °C at + 90 °C ambient.
 *** **Incremental Current:** The minimum typical current at which the inductance will be decreased by 5 % from its initial zero DC value.



MECHANICAL SPECIFICATIONS

Terminal Strength: 3 pounds pull per MIL-STD-202, Method 211, Test Condition A except 180° rotation for a total of 540 °C

Weight: IMS-2 = 0.30 grams maximum

MATERIAL SPECIFICATIONS


Encapsulant: Epoxy

Standard Terminal: #24 AWG tinned copper

TEST EQUIPMENT*

- H/P 4342A Q-Meter
- Measurements Corporation Megacycle Meter, Model 59
- Wheatstone Bridge

* Test procedures per MIL-PRF-15305



INDUCTANCE RANGE AND MILITARY STANDARD			
INDUCTANCE RANGE		MATERIAL	
FROM	TO	CORE	SHIELD
0.10 μH	100 μH	Powdered Iron	Powdered Iron
120 μH	560 μH	Ferrite	Ferrite

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215

ORDERING INFORMATION				
IMS-2	10 μH	± 10 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION														
<table border="1"> <tr><td>I</td><td>M</td><td>S</td><td>0</td><td>2</td></tr> </table> <p>MODEL</p>	I	M	S	0	2	<table border="1"> <tr><td>E</td><td>R</td></tr> </table> <p>PACKING CODE</p>	E	R	<table border="1"> <tr><td>1</td><td>0</td><td>0</td></tr> </table> <p>INDUCTANCE VALUE</p>	1	0	0	<table border="1"> <tr><td>K</td></tr> </table> <p>TOL.</p>	K
I	M	S	0	2										
E	R													
1	0	0												
K														



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.