



# Frontier Electronics Corp.

667 E. COCHRAN STREET, SIMI VALLEY, CA 93065

TEL: (805) 522-9998 FAX: (805) 522-9989

E-mail: [frontiersales@frontierusa.com](mailto:frontiersales@frontierusa.com)

Web: <http://www.frontierusa.com>

## 5A SUPER FAST RECOVERY RECTIFIER


### SF50-005-LFR THRU SF50-06-LFR

#### FEATURES

- LOW POWER LOSS, HIGH EFFICIENCY
- LOW FORWARD VOLTAGE
- HIGH CURRENT CAPABILITY
- HIGH SPEED SWITCHING
- HIGH RELIABILITY
- HIGH SURGE CAPABILITY
- ROHS

#### MECHANICAL DATA

- CASE: MOLDED PLASTIC, DO201AD, DIMENSIONS IN INCHES AND (MILLIMETERS)
- EPOXY: UL 94V-0 MOLDING COMPOUND
- LEADS: MIL-STD-202E, METHOD 208C GUARANTEED
- MOUNTING POSITION: ANY
- WEIGHT: 1.2 GRAMS



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	SF50 -005-LFR R	SF50 -01-LFR	SF50 -015-LFR R	SF50 -02-LFR	SF50 -03-LFR	SF50 -04-LFR	SF50 -05-LFR	SF50 -06-LFR	UNITS
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	$V_{RRM}$	50	100	150	200	300	400	500	600	V
MAXIMUM RMS VOLTAGE	$V_{RMS}$	35	70	105	140	210	280	350	420	V
MAXIMUM DC BLOCKING VOLTAGE	$V_{DC}$	50	100	150	200	300	400	500	600	V
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 0.375"(9.5mm) LEAD LENGTH AT TA=55°C	$I_O$	5.0								A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD	$I_{FSM}$	150								A
TYPICAL JUNCTION CAPACITANCE (NOTE 1)	$C_J$	50				30				PF
TYPICAL THERMAL RESISTANCE (NOTE 2)	$R_{\theta ja}$	30								°C/W
STORAGE TEMPERATURE RANGE	$T_{STG}$	- 55 TO + 150								°C
OPERATING TEMPERATURE RANGE	$T_{OP}$	- 55 TO + 150								°C

#### ELECTRICAL CHARACTERISTICS ( $A_T T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	SF50 -005-LFR	SF50 -01-LFR	SF50 -015-LFR R	SF50 -02-LFR	SF50 -03-LFR	SF50 -04-LFR	SF50 -05-LFR	SF50 -06-LFR R	UNITS
MAXIMUM FORWARD VOLTAGE AT $I_O$ DC	$V_F$	0.95			1.25		1.85			V
MAXIMUM REVERSE CURRENT AT 25°C	$I_R$	10								μA
MAXIMUM REVERSE CURRENT AT 100°C	$I_R$	100								μA
MAXIMUM REVERSE RECOVERY TIME (NOTE 3)	$T_{RR}$	35								nS

- NOTE: 1. MEASURED AT 1 MHZ AND APPLIED REVERSE VOLTAGE OF 4.0 VOLTS  
 2. BOTH LEADS ATTACHED TO HEAT SINK 20x20x1t(mm) COPPER PLATE AT LEAD LENGTH 5mm  
 3. REVERSE RECOVERY TEST CONDITIONS:  $I_F=0.5A$ ,  $I_R=1.0A$ ,  $I_{RR}=0.25$

# RATINGS AND CHARACTERISTIC CURVE SF50-005-LFR THRU SF50-06-LFR

FIG. 1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG. 2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3-TYPICAL REVERSE CHARACTERISTICS




FIG. 4-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 6-TYPICAL JUNCTION CAPACITANCE

