



11	26.00	26.00	24.50		
10	24.00	18.00	22.50		
9	22.00	16.00	20.50		
8	20.00	14.00	18.50		
7	18.00	12.00	16.50		
6	16.00	10.00	14.50		
5	14.00	8.00	12.50		
4	12.00	6.00	10.50		
3	10.00	4.00	8.50		
2	8.00	2.00	6.50		
POS.	DIM. A	DIM. B	DIM. C		
12	26.00	22.00	26.50		
13	30.00	24.00	28.50		
14	32.00	26.00	30.50		
POS.	DIM. A	DIM. B	DIM. C		

②	定位片	Spces	Copper alloy	黄铜镀锡
①	插座	1PCS	Copper alloy	黄铜镀锡
	PART NAME:	QTY	Material: High-temperature plastic, OZON: 100000, 材料: 耐高温塑料, 牌号: 本色, 黄铜	
			DESCRIPTION: 插座	

GENERAL TOLERANCES		— 默认值	
DIM	TOL	DIM	DEG
K, X	±0.20	K, X, Y	±0.00°
K, IX	±0.25	L, IX	±1.00°
K, IXX	±0.25	L, IXX	±1.00°

DRAW :	材料	2016.06.01
DESIGN :	材料	2016.06.01
CHECK :	材料	2016.06.01
APPROVED :	材料	2016.06.01
CUSTOMER DRAWING	客户图版	

名称 TITLE:	2.00 Pitch HT Connector
SERIES:	
P/N:	
REV. 1.00	SCALE N/A

DRAW NAME:	HY2.0-A 贴片式连接器
DRAW NO.	
UNIT:	mm
SHEET:	1/1

版本号  
Version Number  
产品编码  
PART NUMBER