

NOTES:

MATERIAL


- 1.Insulator Material:PBT+30%GF(UL94V-0)
- 2.Contact Material : Brass
- 3.Contact Plating :
AWP xx-8240-T : Gold flash over Ni
AWP xx-8540-T : Tin over Ni

ELECTRICAL

- 1.Current Rating : 3AMP
- 2.Voltage Rating : 500V AC/DC
- 3.Withstand Voltage : 1000V AC/DC
- 4.Contact Resistance : 20mΩ max
- 5.Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

- 1.Operation Temperature: -40°C to +105°C
- 2.Packing: Tray



Section A-A

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	21.12.2009	Dean	ASSMANN WSW-No. AWP xx-8x40-T
X.X	±0.40					Approved	21.12.2009	Hellwig	
X.XX	±0.25								
X.XXX	±0.15								
Angle	±3°								Drawing-No.
								ASS 2261A CO	rev01
								Replace	Sheet
		①	Drawn	21.12.2009	Dean				
		Id.	Modification	Date	Name				

Drawing-No.
ASS 2261A CO rev01

Replace Sheet

