

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [31068-1072](#)
Status: **Active**
Overview: H-DAC 64™ Connector System
Description: 2.54mm H-DAC 64™, 4 Way Male Housing Assembly, Single Row, Polarization C, with Xmas Tree Attachment

Documents:

[3D Model](#) [Application Specification AS-31067-100 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Crimp Housings
Series	31068
Application	Power, Wire-to-Board
Comments	Polarization Option C, Brown
Overview	<u>H-DAC 64™ Connector System</u>
Product Name	H-DAC 64™
UPC	756054393208

Physical

Circuits (maximum)	4
Circuits Detail	4
Color - Resin	Brown
Gender	Male
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Modified Polystyrene, Polyester
Net Weight	2.393/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Ports	1
Stackable	No
Temperature Range - Operating	-40°C to +100°C

Electrical

Current - Maximum per Contact	11A, 9A
-------------------------------	---------

Material Info

Reference - Drawing Numbers

Application Specification	AS-31067-100
Sales Drawing	SD-31110-003




image - Reference only

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[31068Series](#)

Mates With

HDAC 64™, 4 Way Receptacle Assembly
[31068-1012](#)

Use With

See Product Spec