EPCOS

SAW Components


Data Sheet X 7251 D



Duroplast package **SIP5D**

Features

- IF filter for digital TV
- Switchable between two bandwidths
- Optimized for cascade of two devices
- Standard IC package




Dimensions in mm, approx. weight 0,5 g

Terminals

- Tinned CuFe alloy

Pin configuration

1	Input
2	Switching input
3	Chip carrier – ground
4	Output
5	Output



Type	Ordering code	Marking and package according to	Packing according to
X 7251 D	B39362-X7251-N201	C61157-A1-A21	F61074-V8049-Z000

Maximum ratings

Operable temperature range	T_A	–25/+65	˚C	
Storage temperature range	T_{stg}	–40/+85	˚C	
DC voltage	V_{DC}	5	V	between any terminals
AC voltage	V_{pp}	10	V	between any terminals

Characteristics of channel 1 (switching pin 2 connected to ground)

Reference temperature: T_A = 25 °C
Terminating source impedance: Z_S = 50 Ω
Terminating load impedance: Z_L = 2 kΩ || 3 pF


		min.	typ.	max.	
Insertion attenuation	α				
Reference level for the following data 36,17 MHz		19,5	21,0	22,5	dB
Pass bandwidth					
$\alpha_{rel} \leq$ 1,5 dB	$B_{1,5dB}$	7,4	7,7	8,0	MHz
$\alpha_{rel} \leq$ 3 dB	B_{3dB}	7,7	8,0	8,3	MHz
$\alpha_{rel} \leq$ 15 dB	B_{15dB}	8,6	8,9	9,2	MHz
$\alpha_{rel} \leq$ 30 dB	B_{30dB}	8,8	9,4	10,0	MHz
Relative attenuation	α_{rel}				
Lower sidelobe 25,00 ... 31,15 MHz		35,0	41,0		dB
Upper sidelobe 41,15 ... 42,00 MHz		31,0	37,0		dB
42,00 ... 45,00 MHz		37,0	44,0		dB
Reflected wave signal suppression					
1,1 µs ... 6,0 µs after main pulse (test pulse 250 ns, carrier frequency 36,17 MHz)		42,0	50,0	—	dB
Feedthrough signal suppression					
1,3 µs ... 1,2 µs before main pulse (test pulse 250 ns, carrier frequency 36,17 MHz)		—	50,0	—	dB
Group delay ripple (p-p)	$\Delta\tau$				
32,25 ... 40,05 MHz		—	50	—	ns
Impedance at 36,17 MHz					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1,7 ‖17,3	—	kΩ || pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	2,4 ‖ 4,3	—	kΩ || pF
Temperature coefficient of frequency	TC_f	—	–72	—	ppm/K


Characteristics of channel 2 (switching pin 2 connected to pin 1)

Reference temperature: T_A = 25 °C
Terminating source impedance: Z_S = 50 Ω
Terminating load impedance: Z_L = 2 kΩ || 3 pF


		min.	typ.	max.	
Insertion attenuation	α				
Reference level for the following data 36,17 MHz		19,5	21,0	22,5	dB
Pass bandwidth					
$\alpha_{rel} \leq$ 1,5 dB	$B_{1,5dB}$	6,4	6,7	7,0	MHz
$\alpha_{rel} \leq$ 3 dB	B_{3dB}	6,7	7,0	7,3	MHz
$\alpha_{rel} \leq$ 15 dB	B_{15dB}	7,7	8,0	8,3	MHz
$\alpha_{rel} \leq$ 30 dB	B_{30dB}	7,9	8,5	9,1	MHz
Relative attenuation	α_{rel}				
Lower sidelobe 25,00 ... 31,55 MHz		35,0	41,0		dB
Upper sidelobe 40,75 ... 45,00 MHz		33,0	38,0		dB
Reflected wave signal suppression					
1,1 µs ... 6,0 µs after main pulse (test pulse 250 ns, carrier frequency 36,17 MHz)		42,0	50,0	—	dB
Feedthrough signal suppression					
1,3 µs ... 1,2 µs before main pulse (test pulse 250 ns, carrier frequency 36,17 MHz)		—	50,0	—	dB
Group delay ripple (p-p)	$\Delta\tau$				
32,75 ... 39,55 MHz		—	50	—	ns
Impedance at 36,17 MHz					
Input: $Z_{IN} = R_{IN} \parallel C_{IN}$		—	1,5 ‖20,9	—	kΩ || pF
Output: $Z_{OUT} = R_{OUT} \parallel C_{OUT}$		—	2,4 ‖ 4,3	—	kΩ || pF
Temperature coefficient of frequency	TC_f	—	–72	—	ppm/K

Frequency response of channel 1







Frequency response of channel 1




Time domain response of channel 1




Frequency response of channel 2






Frequency response of channel 2



Time domain response of channel 2



Published by EPCOS AG
Surface Acoustic Wave Components Division, SAW CE MM PD
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2003. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.