



CW INDUSTRIES130 James Way
Southampton, PA 18966

Phone: 215-355-7080 • Fax: 215-355-1088

Email: info@cwind.com • Website: <http://www.cwind.com>**Item # GRB238D8SERIES, GRB Series Full Size Sealed Rocker Switches**
[Specifications](#) · [Materials](#) · [Technical Information](#)
Specifications

Circuitry	SPDT
Switch Function	ON-OFF-ON
Electrical Ratings	10A 28VDC 16(4)A 125V/250VAC 16A 12VDC
IP Level	65
Mounting	21 x 35
Actuator Color	Amber Black Green Red
Housing Color	Black
C1	N
Polarization	N
Actuator Legend	Various
Illumination	Non Illuminated
Terminal	0.250 Quick Connect (SQ) Solder
Fitting	Snap-In
Options	 <p>Reference Lamp Chart larger image</p>
Optional Connector	Not Available
Compliance	

Materials

Frame Material	Nylon (UL: 94V-2)
Actuator Material	Nylon (UL: 94V-2) PC (UL: 94V-2)
Terminal Material	Copper Alloy

Technical Information

Operating Temperature	-25 to 85 °C
Maximum Contact Resistance	50m ohm
Minimum Insulation Resistance	DC 500VM 100M OHM
Dielectric Strength (AC) (1 Minute)	1500 °C
Mechanical Life	> 100,000 Cycles
Maximum Solderability of Terminals (Per 3 Seconds)	350 °C