



Multi-Protocol MPR 6000 RFID Card

EPC Class 0/1 and 0+ in PCMCIA Type II Pkg.

Compact Efficient Low Cost

Product Features

Standard 68-Pin PCMCIA Type II PC Card™

Multi Protocol

- EPC Class 0 (read only)
- EPC Class 1 (read and program)
- Class 0+ (read and program)
- Firmware Upgrade (UHF G2 & others)

Multiple Antenna Ports

- Two Separate Antennas
- 50 Ohm MMCX Coax Connectors

Certified Compliance to FCC Part 15

- FCC ID: NTTWJMPR6XXX



Just plug it in, install it and read tags...

WJ's MPR 6000 RFID Card provides breakthrough performance in a standard PCMCIA Type II package. These readers represent a new level for size, standards-based compatibility, ease of use and performance. Each RFID Card includes the analog RF, digital circuitry and embedded firmware required for EPC Class 0 and EPC Class 1 operation. The modular design is flexible, and a simple firmware upgrade is all that is required to incorporate future standards like UHF Gen 2. The MPR 6000 leverages the common PCMCIA Type II PC Card™ standard for ease of use. Plug it into any PCMCIA Type II socket and operate it via a simple WJ GUI program. The standard PCMCIA control interface (68-pin parallel bus) coupled with a simple but powerful command set allows for fast creation of custom applications. These readers enable a host of reader/programmer solutions including handhelds, printers, smart packaging, material handling and industrial products for today and the future.

Copyright WJ Communications March 2006. Subject to change without notice. All trademarks, trade names, service marks, and logos remain the property of the rightful owners



Multi-Protocol MPR 6000 RFID Card

Technical Specifications

Operating Frequency

- UHF 902-928 MHz (U.S. ISM)
- Frequency Hopping

Protocol Support

- 0.5W Transmit Power
- EPC Class 0 and Class 1
- Class 0+ Protocol

Regulatory Compliance by WJ


- Part 15 FCC ID: NTTWJMPR6XXX

Power Supply

- 5VDC Nominal
- 150-250mA Average Current
- 750mA Peak Current

Temperature

- 0 to 40 C Operating
- -20 to 70 C Storage



NOTES:

1. DIMENSIONS ARE EXPRESSED IN INCHES.
2. TOLERANCE .XXX ± .015
.XX ± .02