

APPLICATION

Home, Office, Internet Bar

FEATURES

- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- USB/RS-232 communication port and RJ-11 protection

PHASE (ONLY FOR ONLINE UPS)

Phase: 1-phase in / 1-phase out

INPUT

Capacity: 2000 VA / 1200 W
Voltage: 110/120 VAC or 220/230/240 VAC
Voltage Range: 81-145 VAC / 162-290 VAC
Frequency Range: 60/50 Hz (auto sensing)

OUTPUT

AC Voltage Regulation (Batt. Mode) : ±10%
Frequency Range (Batt. Mode): 60 Hz or 50 Hz ±1 Hz
Transfer Time: Typical 2 ~ 6 ms,
Waveform (Batt. Mode): Simulated Sine Wave

BATTERY

Battery Type: 12 V/9 Ah
Battery Number: 2
Typical Recharge Time: 4-6 hours up to 90% capacity



SAFETY STANDARD APPROVAL



PROTECTION

Full Protection: Overload, Discharge, and Overcharge Protection

PHYSICAL

Output Receptacles: India, French, Schuko, NEMA, and IEC ions
Dimension: 397mm(L) x 146mm(W) x 205mm(H)
Net Weight (kgs): 11.5

OPERATING ENVIRONMENT

Humidity: 0-90 % RH @ 0- 40°C (non-condensing)
Noise Level: Less than 40dB

MANAGEMENT

Optional USB/RS-232 Port: Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC8

This content is subject to change, please refer to specification for more detail.
 FSP reserve the right to change the content without prior notice