




HEYClip™ Nylon Push Screws

Threaded Mounting Hole	PART NO.		DESCRIPTION	PART DIMENSIONS									
	Natural	Black		A Head Height		B Overall Length		C Head Diameter		Push In Force Max.		Pull Out Force Min.	
				in.	mm.	in.	mm.	in.	mm.	LB	N	LB	N
M3	11500	11500B	PS-M3X0.5X8.5MM	.10	2,5	.33	8,5	.22	5,5	7	30	11	50
M4	11501	11501B	PS-M4X0.5X9.5MM	.12	3,0	.37	9,5	.29	7,3	8	35	20	90
M5	11502	11502B	PS-M5X0.5X12.5MM	.14	3,5	.49	12,5	.33	8,5	8	35	22	100
M6	11503	11503B	PS-M6X0.5X15.0MM	.18	4,5	.59	15,0	.39	10,0	8	35	27	120
M8	11504	11504B	PS-M8X0.5X18.0MM	.22	5,5	.71	18,0	.51	13,0	9	40	31	140


- Installs like a traditional nylon push rivet but removable/reusable
- Remove by unscrewing like a traditional threaded fastener
- Saves time by installing with finger-tip pressure
- Low insertion force but high extraction force



HEYClip™ Barbed Push Fasteners

WLL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSIONS							
MOUNTING HOLE DIA.		ASSEMBLED PANEL THICKNESS				Black	A Length		B Head Height		C Head Diameter		
in.	mm.	in.	mm.	in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.157	4,0	.08	2,1	.17	4,3	11530	HBPF 157-339-315 BLACK	.34	8,6	.04	1,0	.31	8,0
		.08	2,1	.28	7,2	11531	HBPF 157-437-315 BLACK	.44	11,1				
		.22	5,7	.42	10,7	11532	HBPF 157-591-315 BLACK	.59	15,0				
		.08	2,1	.17	4,3	11533	HBPF 157-339-472 BLACK	.34	8,6	.06	1,5	.47	12,0
		.08	2,1	.28	7,2	11534	HBPF 157-437-472 BLACK	.44	11,1				
		.22	5,7	.42	10,7	11535	HBPF 157-591-472 BLACK	.59	15,0				
.187	4,8	.08	2,1	.17	4,3	11536	HBPF 187-339-315 BLACK	.34	8,6	.04	1,0	.31	8,0
		.08	2,1	.28	7,2	11537	HBPF 187-437-315 BLACK	.44	11,1				
		.22	5,7	.42	10,7	11538	HBPF 187-591-315 BLACK	.59	15,0				
.250	6,4	.08	2,1	.17	4,3	11539	HBPF 250-339-472 BLACK	.34	8,6	.06	1,5	.47	12,0
		.08	2,1	.28	7,2	11540	HBPF 250-437-472 BLACK	.44	11,1				
		.22	5,7	.42	10,7	11541	HBPF 250-591-472 BLACK	.59	15,0				


- Saves time by installing with finger-tip pressure – no tools required!
- Low insertion force but high extraction force



HEYClip™ Fastener Plug

WILL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSIONS					
MOUNTING HOLE DIA.		MAX. ASSEMBLED PANEL THICKNESS				Black	A Length		B Head Height		C Head Diameter
in.	mm.	in.	mm.	Black	in.		mm.	in.	mm.	in.	mm.
.150	3,8	.311	7,9	9001	FP 150-311	.45	11,5	.07	1,8	.31	8,0

Standard color black. For other colors consult Heyco.



	PS & HBPF	FP
Material	Nylon 6/6	Acetal (POM)
Flammability Rating	94V-2	94-HB
Temperature Range	-40°F (-40°C) to 185°F (85°C)	-4°F (-18°C) to 220°F (104°C)