


Schottky Barrier Rectifier

SS22 ~ SS220

■ Features

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications



■ Absolute Maximum Ratings Ta = 25°C unless otherwise specified

Parameter	Symbol	SS 22	SS 24	SS 26	SS 28	SS 210	SS 212	SS 215	SS 220	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	20	40	60	80	100	120	150	200	V
Surge Peak Reverse Voltage	V _{RSM}	14	28	42	56	70	84	105	140	
Maximum DC Blocking Voltage	V _{DC}	20	40	60	80	100	120	150	200	
Instantaneous Forward Voltage at 1A	V _F	0.55		0.7		0.85		0.95		
Averaged Forward Current	I _O			2						A
Peak forward surge current	I _{FSM}			50		40				
Maximum DC Reverse Current at rated DC blocking voltage	I _R T _A =25°C T _A =100°C		0.5 5		0.3 3					mA
Typical Junction Capacitance *1	C _j	160		80						pF
Typical thermal resistance *2	R _{thJA}			50						°C/W
Junction Temperature	T _j			150						°C
Storage Temperature	T _{stg}			-55 to 150						

* 1 Measured at 1MHz and applied reverse voltage of 4V D.C

* 2 P.C.B. mounted with 2" × 2" (5×5 cm) copper pad areas.

■ Marking

NO.	SS22	SS24	SS26	SS28	SS210	SS212	SS215	SS220
Marking	SS22	SS24	SS26	SS28	SS210	SS212	SS215	SS220

Schottky Barrier Rectifier

SS22 ~ SS220

■ Typical Characteristics

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




Fig.6-Typical Transient Thermal Impedance

