

# J84-4300 Wipe-key Keyboard



*Actual product may vary from the image shown*

**Slim, low profile, compact keyboard with integrated pointing device:** The J84-4300 offers an IP55 rating for protection against dust and spraying liquids. It's ideal for applications requiring frequent disinfection for elimination of germs. Uses include diagnostics equipment, medical carts, rack mount servers, laboratories, and kiosks.

## Facts & Features

- Membrane technology provides dust, dirt, and spraying water protection.
- Designed for continuous use – more than 10 Million key operations
- High reliability and uniquely precise tactile keying
- Full 87 US key layout
- Ultra slim - overall height only 19 mm
- Uses Standard Operating System Drivers
- Ideal for use with space limitations

## Technical Data:

**Housing and Key Color:**  
Black

**Weight**  
Without Packaging 600 g / 1.3 lbs  
With Packaging 730 g / (Approx)1.6 lbs

**Cable Length:**  
Approx. 1.62 m

**Keyswitch Lifetime:**  
Key life: 10 Million operations

**Storage Temperature:**  
-20°C to +60°C / -4° F to 140° F

## Technical Data Cont:

**Layout:**  
87 US key layout

**Current Consumption:**  
40mA (MAX)

**Interface:**  
USB

**Agency Approvals:**  
CE  
FCC  
Class B  
BSMI  
RoHS

**System Requirements:**  
USB connection

**Delivery Volume:**  
J84-4300, manual

**Compatible Operating Systems:**  
Win 98SE, ME, 2000, XP, XP x 64, Vista, Windows

**Packaging Unit:**  
20 keyboards per master carton  
12 master cartons per pallet (240 pcs.)

**Dimensions:**  
Keyboard: 370 x 139 x 19 mm  
14.5" x 5.5" x .75"  
Packaging: 396 x 210 x 43 mm  
15.6" x 8.3" x 1.7"

**Warranty:**  
2 years



**Operating Temperature:**

0° C to +60° C / 31° F to 140° F

**Humidity:**

0~95% RH

**Order Description**

Service Design	Order Number	Interface	Color
Medium Use	J84-4300LUAUS-2	USB	Black

Other country versions available upon request. (Special conditions apply)

Cherry Americas, LLC  
11200 88th Avenue  
Pleasant Prairie, WI 53158  
USA  
Phone: 262.942.6508  
Internet: [www.cherryamericas.com](http://www.cherryamericas.com)

E-Mail: [cep\\_sales@zf.com](mailto:cep_sales@zf.com)

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2016 Cherry Americas, LLC, Rev Date: January 6, 2016