



Features

- ✧ For IF SAW filter
- ✧ High attenuation
- ✧ Single-ended operation
- ✧ Dual In-line Package
- ✧ RoHS compliant (2002/95/EC), Pb-free

Specifications

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	106.85	107	107.15
Insertion Loss	dB	-	30	32
3 dB Bandwidth	MHz	24	24.06	-
40 dB Bandwidth	MHz	-	24.76	24.8
45 dB Bandwidth	MHz	-	24.81	25
50 dB Bandwidth	MHz	-	24.86	35.7
Passband Variation	dB	-	1.2	1.5
Absolute Delay	usec	-	3.74	4
Ultimate Rejection(f0±15MHz)	dB	50	51	-
Material Temperature coefficient	KHz/°C	-10.1		
Substrate Material	-	YZ LN		
Ambient Temperature	°C	25		
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-45	-	+105
DC Voltage	V	0		
Input Power	dBm	-	-	10
ESD Class	-	1A		
Package Size	DIP3512 (35.0x12.8x4.7mm3)			

Notes:


1. All specifications are based on the test circuit shown;
2. In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
4. This is the optimum impedance in order to achieve the performance show.



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN10708		
Rev. Date	2009-10-12		
Ver.	1.0	Page 1/3	

Matching Configuration




L1=56nH

Source/Load Impedance=50 ohm

Notes - Component values may change depending
on board layout.

Package Dimension



Pad Configuration:

Input 1
Output 5
Ground All Others

Marking Configuration:

- 1) SIPAT: Manufacturer Name
- 2) LBN10708: Part Number
- 3) XXYY: Date(Year/month)
- 4) ZZ: Identified Code

Package: DIP3512

Unit: mm




SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN10708	
Rev. Date	2009-10-12	
Ver.	1.0	Page 2/3



Typical Performance


Frequency Response



Horizontal: 10MHz/Div

Vertical: 10dB/Div


Passband Response



Horizontal: 10MHz/Div

Vertical: 0.5dB/Div


Group Delay Variation($f_0 \pm 12$ MHz)



Horizontal: 5MHz/Div

Vertical: 100ns/Div


Phase Linearity($f_0 \pm 12$ MHz)




Horizontal: 5MHz/Div

Vertical: 20deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number

LBN10708

Rev. Date

2009-10-12

Ver.

1.0

Page 3/3