General Cable Product Data Sheet

Part Number: C3208	Revision Level: 0	Date: 7/7/2007

6P 22 7/30 TC FEP OAS FLEX PVDF **TYPE CMP**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#22 AWG 7/30 Tinned Copper	0.030” nom.
Insulation:	0.006" Wall FEP	0.042" nom.
Pairing	12 conductors into 6 pairs @ 1.50” LHL.	
Cable:	6 pairs @ 3.50” LHL, aluminum/polypro (foil in) & # 24 7/32 TC drain wire.	0.217" nom.
Jacket:	0.010"Wall PVDF – Natural -Plenum ripcord under jacket.	0.237" +/- 0.006"
Print Legend:	***CAROL (R) 22 AWG -- C3208 -- 150C E111240-8 CMP(UL) C(UL) -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	150C
SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms (CMP)
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black & Yellow
2	Red & Purple
3	Dark Blue & Brown
4	Orange & Dark Green
5	Pink & Gray
6	Tan & White

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.