



## Connectors System AC 164 Cables

### AC 164 ALSS/415 200 white

Extension Cable Plug, 4 pole, white, Coding: 1 (Mains), Cable Type: H05VV-F, Core Cross-Section: 1.5 mm<sup>2</sup>, Fire Class: Eca, Length: 2.00 m, Voltage Rating: 250/400 V, Current Rating: 16 A



#### Order Info

|                                    |   |
|------------------------------------|---|
| <b>Reference Number (ref. no.)</b> | 14815420                                      |
| <b>Applications</b>                | Lighting, Installation, Electrical Appliances |
| <b>PU</b>                          | 25  |

#### Type

|  |                      |
|--|----------------------|
| <b>Type</b>                                  | Extension Cable Plug |
| <b>Number of poles</b>                       | 4 pole               |
| <b>Colour</b>                                | white                |
| <b>Coding</b>                                | 1 (Mains)            |
| <b>PE Function</b>                           | yes                  |
| <b>Protection Against Incorrect Plugging</b> | yes                  |
| <b>Latch</b>                                 | yes                  |

#### Technical Data

|   |  |
|---|--|
| <b>Voltage Rating</b>                     | 250/400 V  |
| <b>Current Rating</b>                     | 16 A   |
| <b>Insulating Material</b>                | PA 6.6   |
| <b>Contact Material</b>                   | Brass  |
| <b>max. Ambient Temperature Operation</b> | 70 °C  |
| <b>IP Code</b>                            | IP20   |
| <b>IP Code when Plugged</b>               | IP40   |
| <b>Type of Conductor Flexible</b>         | yes  |
| <b>Stripping Length</b>                   | 7.0 mm   |
| <b>Dismantling Length PE</b>              | 26.0 mm  |
| <b>Dismantling Length</b>                 | 33.0 mm  |
| <b>Cable Type</b>                         | H05VV-F  |
| <b>Core Cross-Section</b>                 | 1.5 mm <sup>2</sup>                                  |
| <b>Fire Class</b>                         | Eca  |
| <b>Length</b>                             | 2.00 m   |
| <b>Approbation EN61535</b>                | AC 164_EN61535_20190125_DEKRA_ENEC_71-107174_web.pdf |