

# Han 16HPR EasyCon cover 3XM32



Part number	19 40 016 9903
Specification	Han 16HPR EasyCon cover 3XM32
HARTING eCatalogue	https://b2b.harting.com/19400169903

Image is for illustration purposes only. Please refer to product description.

#### Identification

Hoods/Housings
Han <sup>®</sup> HPR EasyCon
Mounting cover
for surface mounted housings for hoods

#### Version

Locking type	Screw locking
Size	16 HPR
Cable entry	3x M32
Field of application	Hoods/housings for harsh outdoor environments
Details	Not compatible to cable glands 19 00 000 5014, 19 00 000 5015 and 19 00 000 5022

# **Technical characteristics**

Tightening torque	6 Nm Mounting cover 6 Nm Distance bolt 6 Nm Fixing screws
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65 IP68 IP69 / IPX9K acc. to ISO 20653
Type rating acc. to UL 50 / UL 50E	4 4X 12

Page 1 / 2 | Creation date 2020-03-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

# Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076

### Commercial data

Packaging size	1
Net weight	191.75 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors