



Servo motor EMMT-AS-100-L-HS-RS

Part number: 5255534

FESTO



Data sheet

Feature	Value
Electrical connection 1, connection technology	M23x1
Electrical connection 1, connection type	Hybrid plug
Electrical connection for input 1, connection pattern	00995913
Concentricity, coaxiality, axial runout according to DIN SPEC 42955	N
Detent torque	< 1.0% of peak torque
Mounting position	Any
Rotor position sensor for manufacturer designation	ECL 1319
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Information on max. installation height	with 1,000 m and longer only with derating of -1.0% per 100 m
Contamination level	2
Note on degree of protection	IP40 for motor shaft without rotary shaft seal IP65 for motor shaft with rotary shaft seal IP67 for motor housing, incl. connection technology
Note on ambient temperature	Up to 80 °C with derating of -1.75% per degree Celsius
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Measuring flange	300 x 300 x 20 mm, steel
Balancing quality	G 2.5
Motor type as per EN 60034-7	IM B5 IM V1 IM V3
Certificate issuing authority	UL E342973
Electrical connection 1, number of pins/wires	15
Max. winding temperature	155 °C
Max. installation height	4000 m
Rotor position encoder for DC operating voltage	5 V
Max. mechanical speed	13000 1/min
Number of pole pairs	5
Storage lifetime, under nominal conditions	20000 h
Electric time constant	15.8 ms
Cross inductivity Lq (phase)	11.8 mH
Winding longitudinal inductivity Ld (phase)	8.7 mH
Rotor position encoder for DC operating voltage range	3.6 V ... 14 V
Standstill torque constant	1.75 Nm/A
Rotor position encoder for absolutely detectable revolutions	1

Feature	Value
Rotor position encoder system accuracy angle measurement	-65 arcsec ... 65 arcsec
Thermal resistance	0.46 K/W
Rotor position encoder for positional values per revolution	524288
Thermal time constant	71 min
Type code	EMMT-AS
Rotor position sensor	Absolute encoder, single-turn
Rotor position sensor interface	EnDat® 22
Rotor position sensor measuring principle	Inductive
Temperature monitoring	Digital motor temperature transmission via EnDat® 2.2
Max. rotational speed	3770 1/min
Nominal rotary speed	2700 1/min
Continuous stall current	7 A
Motor constants	1.54 Nm/A
Nominal operating voltage DC	565 V
Motor nominal power	2030 W
Motor nominal current	4.7 A
Rotor position sensor resolution	19 bit
Phase-phase winding resistance	1.49 Ohm
Winding inductance phase-phase	15.7 mH
Type of winding switch	Star inside
Peak current	28.6 A
Voltage constant, phase-to-phase	106 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive As per EU RoHS directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-20 °C ... 70 °C
Relative air humidity	0 - 90 %
Degree of protection	IP40
Ambient temperature	-15 °C ... 40 °C
Thermal class according to EN 60034-1	F
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	5.77 kgcm ²
Nominal torque	7.2 Nm
Peak torque	30.5 Nm
Stall torque	10.8 Nm
Permissible axial shaft load	200 N
Permissible radial shaft load	1110 N
MTTF, subcomponent	190 years, rotor position sensor
MTTFd, subcomponent	380 years, rotor position sensor
Product weight	8700 g
Interface code, motor out	100A
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Conforms to standard	IEC 60034