


技术参数 SPECIFICATIONS

- 线数 (Poles) : 2~15(30)
- 适用线规 (Applicable wires) : AWG30#~24#
- 适应基板厚度 (Applicable PC board thickness) : 1.2~1.6mm
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 2A
- 接触电阻 (Contact resistance) : $\leq 0.02\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 800V.Ac/1min
- 材料 (Material) :
壳体 (Housing) : 尼龙 (Nylon) UL94V-2(0)
端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)


端子 TERMINAL (SAN)

型号 Type	适用线规 Applicable wires mm' AWG#	电线外径 O.D of wire ins mm	数量 Quantity
HX20008-PT	0.05~0.22	30~24	10000PCS/盘
HX20008-PTB	0.05~0.22	30~24	10000PCS/盘


HX20008-PT (SAN)




HX20008-PTB (SAN)



HX20008-Y (SAN)



安装尺寸 MOUNTING MEASUREMENT



壳体 HOUSING (SAN)

线数 Poles	型号 Type	尺寸 Dimensions (mm)	
		A	B
2	HX20008-2Y	2.0	5.2
3	HX20008-3Y	4.0	7.2
4	HX20008-4Y	6.0	9.2
5	HX20008-5Y	8.0	11.2
6	HX20008-6Y	10.0	13.2
7	HX20008-7Y	12.0	15.2
8	HX20008-8Y	14.0	17.2
9	HX20008-9Y	16.0	19.2
10	HX20008-10Y	18.0	21.2
11	HX20008-11Y	20.0	23.2
12	HX20008-12Y	22.0	25.2
13	HX20008-13Y	24.0	27.2
14	HX20008-14Y	26.0	29.2
15	HX20008-15Y	28.0	31.2
...
30	HX20008-30Y	58.0	61.2