

## **WPANT30120**

## MIMO Antenna - Dual-band Wi-Fi



WPANT30120-R1A

36" long cables with RP-SMA Female (Two connectors)

Note: Different cable and connector style requests can be accommodated.

## **Application**

This is a high gain MIMO Omni-directional antenna. It comes with mounting brackets for installation.

We specialize in developing customized Antenna solutions. Please contact <a href="mailto:sales@worldproducts.com">sales@worldproducts.com</a> with your requirements.

Electrical Properties		
Operating Frequency	2.4 – 2.5 GHz	5.15 – 5.85 GHz
Approximate Antenna Impedance $[\Omega]$	50Ω	50Ω
VSWR (Typical)	< 2:1	< 2:1
Peak Gain [dBi] (Typical)	6 dBi	6 dBi
Polarization	Vertical	Vertical
Accepted Power [W] (Max)	10 Watts	

Mechanical / Environmental Properties		
Antenna Dimensions	7.0" Height x 5.9" dia (178mm x 150mm)	
Antenna Color	White	
Antenna Radome	ABS	
Operating / Storage Temperature	-40°C to +90°C	
Environmental	Meets standards for UL 94V-0	
Hazardous Materials	RoHS Compliant	

Rev: 1.0 March 10, 2016 Page | 1



## Picture



Rev: 1.0 March 10, 2016 Page | 2