



Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311  
Phone: (818) 701-4933  
Fax: (818) 701-4939

## MBR20150FCT

### Features

- High Junction Temperature Capability
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Low Leakage Current
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: type number



### Maximum Ratings

- Operating Junction Temperature : 150°C
- Storage Temperature: - 50°C to +150°C
- Per diode Thermal Resistance 2.2°C/W Junction to Case
- Total Thermal Resistance 1.3°C/W Junction to Case

| MCC Catalog Number | Maximum Recurrent Peak Reverse Voltage | Maximum RMS Voltage | Maximum DC Blocking Voltage |
|--------------------|--|---------------------|-----------------------------|
| MBR 20150 FCT      | 150 V                                  | 105V                | 150 V                       |

## 20 Amp High Voltage Power Schottky Barrier Rectifier 150Volts

### ITO-220AB



### Electrical Characteristics @ 25°C Unless Otherwise Specified


|  |             |                    |   |
|--|-------------|--------------------|---|
| Average Forward Current                              | $I_{F(AV)}$ | 20 A               | $T_C = 155^\circ\text{C}$                             |
| Peak Forward Surge Current                           | $I_{FSM}$   | 180A               | 8.3ms, half sine wave                                 |
| Maximum Instantaneous Forward Voltage<br>MBR20150FCT | $V_F$       | .92V               | $I_{FM} = 10A$<br>$T_J = 25^\circ\text{C}$            |
|  | $V_F$       | .75V               | $I_{FM} = 10A$<br>$T_J = 125^\circ\text{C}$           |
| Maximum Reverse Current At Rated DC Blocking Voltage | $I_R$       | 25 $\mu$ A<br>5m A | $T_J = 25^\circ\text{C}$<br>$T_J = 125^\circ\text{C}$ |

| DIMENSIONS |        |      |       |       |      |
|------------|--------|------|-------|-------|------|
| DIM        | INCHES |      | MM    |       | NOTE |
|            | MIN    | MAX  | MIN   | MAX   |      |
| A          | .583   | .630 | 14.80 | 16.00 |      |
| B          | ---    | .406 | ---   | 10.30 |      |
| C          | .100   | .112 | 2.55  | 2.85  |      |
| D          | .248   | .272 | 6.30  | 6.90  |      |
| E          | ---    | .161 | ---   | 4.10  |      |
| F          | ---    | .071 | ---   | 1.80  |      |
| G          | .512   | .543 | 13.00 | 13.80 |      |
| H          | .100   |      | 2.55  |       |      |
| I          | ---    | .035 | ---   | 0.90  |      |
| J          | ---    | .032 | ---   | 0.80  |      |
| K          | .118   | .134 | 3.00  | 3.40  | Ø    |
| L          | ---    | .189 | ---   | 4.80  |      |
| M          | ---    | .130 | ---   | 3.30  |      |
| N          | .098   | .114 | 2.50  | 2.90  |      |
| O          | ---    | .055 | ---   | 1.40  |      |


Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

[www.mccsemi.com](http://www.mccsemi.com)


**Fig. 1:** Average forward power dissipation versus average forward current (per diode).




**Fig. 2:** Average forward current versus ambient temperature ( $\delta = 0.5$ , per diode).




**Fig. 3:** Non repetitive surge peak forward current versus overload duration (maximum values, per diode).




**Fig. 4:** Relative variation of thermal impedance junction to case versus pulse duration (per diode).




**Fig. 5:** Reverse leakage current versus reverse voltage applied (typical values, per diode).




**Fig. 6:** Junction capacitance versus reverse voltage applied (typical values, per diode).



**Fig. 7:** Forward voltage drop versus forward current (maximum values, per diode).



**Fig. 8:** Thermal resistance junction to ambient versus copper surface under tab (Epoxy printed circuit board, copper thickness: 35 $\mu\text{m}$ ) (STPS20150CG only).





TM

Micro Commercial Components

**Ordering Information :**

| Device         | Packing         |
|----------------|-----------------|
| Part Number-BP | Bulk: 1Kpcs/Box |

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

---

**[www.mccsemi.com](http://www.mccsemi.com)**

---