GP1L55

High Sensitivity Photointerrupter


■ Features

1. Compact package
   (Case height: 8mm)
2. High sensing accuracy
   (Slit width•••Detector: 0.15mm, Emitter: 0.5mm)
3. Easy positioning to PWB with positioning pin

■ Applications

1. Floppy disk drives
2. VCRs, Cassette decks
3. Optoelectronic switches, electronic counters, edge sensors.

■ Outline Dimensions (Unit : mm)



■ Absolute Maximum Ratings (Ta = 25˚C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	50	mA
	*1Peak forward current	I_{FM}	1	A
	Reverse voltage	V_R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V_{CEO}	35	V
	Emitter-collector voltage	V_{ECO}	6	V
	Collector current	I_C	40	mA
	Collector power dissipation	P_C	75	mW
Operating temperature		T_{opr}	- 25 to + 85	˚C
Storage temperature		T_{stg}	- 40 to + 100	˚C
*2Soldering temperature		T_{sol}	260	˚C

*1 Pulse width<=100μs, Duty ratio= 0.01
*2 For 5 seconds

" In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that occur in equipment using any of SHARP's devices, shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest version of the device specification sheets before using any SHARP's device."

■ Electro-optical Characteristics

(Ta = 25˚C)

Parameter			Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage		V_F	I_F = 20mA	-	1.2	1.4	V
	Peak forward voltage		V_{FM}	I_{FM} = 0.5A	-	3	4	V
	Reverse current		I_R	V_R = 3V	-	-	10	μA
Output	Collector dark current		I_{CEO}	V_{CE} = 10V	-	-	10^{-6}	A
Transfer characteristics	Collector Current		Ic	I_F = 2mA, V_{CE} = 2V	0.6	-	-	mA
	Collector-emitter saturation voltage		$V_{CE(sat)}$	I_F = 4mA, I_C = 0.6mA	-	-	1	V
	Response time	Rise time	t_r	V_{CE} = 2V, I_C = 10mA	-	80	400	μs
		Fall time	t_f	R_L = 100Ω	-	70	350	μs

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Collector Power Dissipation vs. Ambient Temperature




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Collector Current vs. Forward Current




Fig. 6 Collector Current vs. Collector-emitter Voltage




Fig. 7 Collector Current vs. Ambient Temperature




Fig. 8 Collector-emitter Saturation Voltage vs. Ambient Temperature





Fig. 9 Response Time vs. Load Resistance



Test Circuit for Response Time




Fig.10 Frequency Response




Fig.11 Collector Dark Current vs. Ambient Temperature




Fig.12 Relative Collector Current vs. Shield Distance (1)





Fig.13 Relative Collector Current vs. Shield Distance (2)



■ Precautions for Use

(1) In case of cleaning, use only the following type of cleaning solvent.
Ethyl alcohol, Methyl alcohol, Isopropyl alcohol

(2) As for other general cautions, refer to the chapter "Precautions for Use".