



Circuit Diagram

NOTE:
 1. Operating Force: 200gf±50gf
 2. Lock Travel : 2.00±0.3mm

⑧	Terminal	6	Brass strip	Plating silver
⑦	Contact	2	Phosphor bronze Plating silver	
⑥	Securing glue	2	PA66	Black
⑤	Spring	1	SUS	Natural
④	Base	1	PBT	Black
③	Crochet Needle	1	SUS	Natural
②	Cover	1	POM	White
①	KNOB	1	POM	Blue
ITEM	PART NAME	QTY.	MATERIAL	FINISHING

PCB Layout(Pattern Side)

APPROVALS		DATE	DRAWING NO.	
DRAWN	G.M.Chen	2015/4/16	PB-22E88-N	
CHECKED			TITLE: PUSH SWITCH	
APPROVALS			ELECTRONICS CO.,LTD	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30 ^{±0.15} 10 ^{±0.20} 5 ^{±0.15}	±0.30 ±0.20 ±0.15	ANGLE	±2°	DRAWING NO.	SHEET 1 OF 1
	A		NEW				APPROVALS						PROJ.