



## Main

Range	Legacy
Product Type	Solid state relay
Maximum output current	50 A AC
Mounting Support	Panel
Network Number of Phases	1 phase
Output Voltage	48...600 V AC
Control Circuit Voltage	3...32 V DC

## Complementary

Holding Current	250 mA
Input Current Limits	5...40 mA
Switch Function	SPST
Contacts Type and Composition	NO
Protection Type	Reverse polarity protection
Tightening Torque	10 lb.in for input 20 lb.in for output
Connections Terminals	Input screw clamp terminal, 1 Output screw clamp terminals, 1
Screw Type	M3.5 M6
Local Signalling	for input status 1 LED (green)
Switching Device	SCR output Zero voltage switching
Maximum Peak Voltage	1200 V
Surge Current	520 A 16.6 ms
Must Release Voltage	1 V
Voltage Drop	<1.8 V on-state AC
Power Factor	with maximum load
Insulating Resistance	1 GΩ
Thermal Resistance	0.63 °C/W

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum I <sup>2</sup> t for fusing	1035 A <sup>2</sup> .s 8.3 ms
Leakage Current	1 mA at off-state
DV/Dt	1000 V/ $\mu$ s off-state
Dielectric Strength	4000 V between input and ground 4000 V between output and ground 4000 V between input and output
Height	1.39 in (35.3 mm)
Width	1.85 in (47.1 mm)
Depth	2.30 in (58.4 mm)
Product Weight	4.76 oz (135 g)

## Environment

Product Certifications	UL CSA CE
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)
Ambient Air Temperature for Storage	-40...257 °F (-40...125 °C)

## Ordering and shipping details

GTIN	03606481106438
------	----------------

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Wiring Diagrams

