

# 935125736710-xxA

In Production



## Appearance & Shape



## Features

- I Ultra High operating temperature
  - EXSC: up to 250°C
- I Low profile (250μm)
- I High stability (temperature, voltage and aging)
- I Low leakage current
- I High reliability

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# 935125736710-xxA



## Specifications

Series	EXSC
Applications	High Reliability
Features	High Temperature
Mounting Method	Wire-bonding/Embedded
Operating Temperature Range	-55°C to 250°C
Size Code (in inch)	1616
L x W (size)	4.07 x4.07mm
Breakdown Voltage (For the rated voltage, please see the FAQ.)	30Vdc
Capacitance	1μF
Thickness	250μm

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.